DS-D47XXCF-1A/P/A2

DS-D47XXCF-1A/P/A2





- Cable package for 5 sqm screen, compatible with Aries Pro Series outdoor 500x1000mm：DS-D4729CF-1AC/P, DS-D4739CF-1AC/P. Default including：power supplies x1, receiving cards x1, HUB boards x1, main power cables x2, main data cables x1, power cable between cabinets x11, data cable between cabinet x11, fixation paltes x10, etc.

▪ Specification

Product Type	
Product Type	Spare Cables Package
Power	
Power Supply	110~220 VAC ± 15%
Working Environment	
Working Temperature	-20 ℃ to +45 ℃ (-4 ℉ to +113 ℉)
Working Humidity	10%~90%RH (No condensation)
Storage Humidity	10%~95%RH (No condensation)
Storage Temperature	-40 ℃ to +60 ℃ (-40℉ to +140 ℉)
General	
Package Dimension (W × H × D)	626 (W) mm ×372 (H) mm × 402 (D) mm
Packing List	Module × 0 Main Network Cable (20 m) × 1 Main Power Cord (10 m) × 2 Cascading Network Cable × 11 Cascading Power Cord × 11 Joint Piece and Screw × 10 Driver IC × 0 Lamp Bead × 0 Power Supply × 1 Mask × 0 Power Input Aviation Plug (with Cord) × 1 Power Output Aviation Plug (with Cord) × 1 Aviation Plug for Network Interface × 1 Internal Network Cable × 1 Receiving Card × 1 Hub Board ×1
Gross Weight	14 kg/1 in 1 (30.86 lb.)

▪ Available Model

DS-D47XXCF-1A/P/A2

▪ Accessory



DS-D4729CF-1AC/P



DS-D4739CF-1AC/P

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®